


## Size and Weight



Weight 3kg

## Material

Material	Aluminum alloy
Color	Anodize silver
Optic Material	PC

## Function

Dimming	4 level dimming / 10 level fine dimming
Mounting	1.5m suspension wire
For tank size	W90 x D60 x H60cm or below

## Specification

Optic Structure	RGB - W, Color Mix Grow Light, Cree LED
Color Temperature(CCT)	6500K Daylight
Operating Voltage / Current	DC-24V / 3A
Input Voltage	AC 100 - 240V
Rated Frequency	50/60 Hz
Lumen Output	4000 Lm
Total Power	78W
Lumen Efficacy	51 Lm/W
Beam angle	80°
LED Life Span	36,000 hrs
RoHS	Yes

## Power supply certificate



www.ATLEDTiS.com




V0310

**ATLEDTiS**  
©2017 ATLEDTiS All rights reserved.

## Warranty

Limited Warranty 1 year

\*Technical data are based on optimum conditions, actual performance may vary.  
Warranty : For more information, please contact ATLEDTiS office or distributors.



# PRO-I

RGB-W COLOR MIX GROW LIGHT  
LED LIGHTING SYSTEM

**ATLEDTiS**

# PRO-1 RGB-W COLOR MIX GROW LIGHT LED LIGHTING SYSTEM

## Simplicity

the ultimate sophistication


It is not just a slogan. With years of lighting and industrial design experience, we have achieved to put the most sophisticated RGB-W color mix technology into just 20mm thick aluminum body. Yet maintain its light quality and both thermal management.

## Optic mix technique

To achieve the best color mixing effect, we choose the best material as our diffuser, ensure the best color mixing quality in the smallest space. Color mix angle is limited within 80 degrees, ensure even color mixing and good light penetration.

## RGB-W

Growth spectrum



RGB-W provide optimum spectrum for plant growth, new design technique takes BRIGHTNESS and COLOR RENDITION into the next level, Red and Green color improves. RGB-W technology was tested, verified and improve by ATLEDTIS in many years.

## Remote control

4lv dimming/10lv fine dimming

One remote controls all, you can control multiple PRO-1 with one single remote. Simply pairing PRO-1 with the remote you want. You can pair as many PRO-1 as you want. Once the PRO-1 paired, other remote cannot control it.



Light Intensity	Pairing
☀️ 100%	☀️ + ☀️
☀️ 75%	
☁️ 50%	Unpairing / Free mode
☁️ 25%	3 sec ☀️

## MagPlug

PRO-1 uses magnetic plug, both end of connector are splash proof. 90 degree plug allows you to choose the cable turns to any direction without worry damaging the cable, ensures safety while using. It is more easy to use and cleaner design.



**20mm**  
Super Slim

**0**  
No button on housing

**W90cm**  
Design for W90cm tank

**Ra90**

PRO-1 uses state of the art **CREE** LED, with ATLEDTIS color mix technology, color rendering can reach up to Ra90.

**4000 lm**

Designed for tank with **W90 x D60cm** and can easily penetrate **H60cm** tank.

**Flickering control**

Double filtering reduce the flickering to the minimum, ensuring users health and LED lifetime.

